



MODELS

KGH-OF-(30, 40, 50, 60, 80, 100)-S KGH-OF-(30, 40, 50, 60, 80, 100)-R GRAB-N-GO HIGH PROFILE CASE

CASE HOLDS 36°F TO 40°F • FORCED AIR REFRIGERATION • OPEN FRONT FRONT LOADING • LED LIGHTING IN CANOPY AND UNDER SHELVES PULL DOWN NIGHT CURTAIN • CASES CAN BE MULTIPLEXED














SELF CONTAINED	Model	Width (inches)	Capacity Cu.ft	Electrical					Weight lbs		Crate Size (inches)		
				Compressor		Total	Total	Required Hard-Wire	No	With			
				Н.Р	F.L.A 115V	Amps 115 V	Amps 230 V	Connection	Crate	Crate	L"	W"	H″
	KGH-OF-30-S	29.2	15.9	3/4	16.0	20.7	N/A	1x 115V	408	542	32.2	32.5	85.4
	KGH-OF-40-S	41	23.3	1	16.2	26.3	N/A	1x 115V	463	633	44	32.5	85.4
	KGH-OF-50-S	50.2	29.1	1	16.2	27.0	N/A	1x 115V	514	728	53.2	32.5	85.4
	KGH-OF-60-S	60.6	35.6	1-1/4	N/A	10.8	9.2	1x 115V + 1x 220V	580	818	63.6	32.5	85.4
	KGH-OF-80-S	78.2	46.6	2 x 1	N/A	11.2	16.4	1x 115V + 1x 220V	752	1049	81.2	32.5	85.4
	KGH-OF-100-S	96.6	58.2	2 x 1	2 x 16.2	2 x 27	N/A	1x 115V + 1x 220V	939	1285	99.6	32.5	85.4

		Width			Required	Weight lbs		
	Model	(inches)	115 Volts Total Amps	B.T.U	Hard-Wire Connection	No Crate	With Crate	
≝	KGH-OF-30-R	29.2	0.85	4793	1x 115V	342	476	
REMOTE	KGH-OF-40-R	41	0.90	6940	1x 115V	353	523	
2	KGH-OF-50-R	50.2	1.30	7565	1x 115V	404	617	
	KGH-OF-60-R	60.6	1.36	9383	1x 115V	463	701	
	KGH-OF-80-R	78.2	1.81	13881	1x 115V	562	860	
	KGH-OF-100-R	96.6	2.60	14921	1x 115V	691	1043	



STANDARD FEATURES

Tempered side glass

Pull down night curtain

CFC free injected foam insulation

Silver colored PVC coated steel front panel

PVC coated steel gray interior

Black steel kick plate

Foamed polystyrene black end panels

Height adjustable shelves can be tilted

Products stop on all shelves

Temperature and defrost regulated by a digital controller

Removable condensate evaporating pan for easy cleaning on self contained units

Slide out condensing unit on self-contained units

Digital thermometer

Leveling feet

OPTIONAL FEATURES

Stainless steel interior and / or exterior

Other colors available

Solid or full view end panels

Additional shelves

Joining Kit and/or Partition and or / product dividers

Price tag molding

Condensate evaporating pan for remote cases

Casters add 4-3/8" to height

Stainless steel legs are adjustable from 5-1/8" to 7-5/8"



3560 NW 56th St

Fort Lauderdale, FL USA 33309

Tel: 786.600.4687 / Toll Free: 844.218.8477 / Fax: 786.661.4100



5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Tel: 514.737.9701 / Toll Free: 888.275.4538 / Fax: 514.342.3854

Toll free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com

Standard Mounting



Levelling Feet

U



Adjustable Legs

Cactors

Optional Mounting

NOTE

These cases are engineered to operate in locations not exceeding 75°F and 55% R.H. These cases are designed to operate using R452a refrigerant. Alternate refrigerants available by special order. O.A. length includes (2) ends at 1-1/2" each. Ventilation grills at front and back cannot be blocked. B.T.U.'s are calculated at 14°F (evaporator) and 90°F (ambient). Remote cases are provided with an expansion valve and a liquid solenoid for pump down evaporating pan must be ordered and 3.3 or 8.3 amps added to the amp load. Remote cases must be hard wired – no plugs.

WARRANTY

One year parts and labor with an additional four years on the compressor (part only)



Hydra - Kool is a registered trademark of MVP Group Corp. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE