REACH-IN BOTTOM-MOUNT SERIES REFRIGERATORS

Features

- CFC free refrigerant and foam insulation
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- 3 adjustable, heavy-duty epoxy coated wire shelves per door
- Condensate heating element built into condensate pan for efficient evaporation of excess water
- Easy to mount 4" casters (lockable in front) are standard with all units
- Locking doors on all units. IB19R/27R door swing is field reversible
- · Self-closing doors that remain open at 90 degrees
- Magnetic gasket can be replaced without any tools
- Exterior: 430 stainless steel
- Interior: 304 stainless steel
- Temperature: 33 to 40°F / 0.5 to 4°C
- R-290 Natural refrigerant

• Electrical: 115/60/1 with NEMA 5-15P plug, 10ft cord















Specifications

DESIGNED TO OPERATE IN AMBIENT TEMPERATURES BETWEEN 40F-90F FOR OPTIMUM PERFORMANCE.

| Model | Doors | Ext. Dimensions W X D X H (In) | Int Dimensions W X D X H (In) | Amps | H.P | Ship Weight |
|--------|-------|--------------------------------|----------------------------------|------|-----|-------------|
| IB19R | 1 | 26.8 X 25.6 X 82.3 | 22.2 X 21.5 X 50.2 | 3 | 1/5 | 295 lbs |
| IB27R* | 1 | 26.8 X 32.7 X 82.3 | 22.2 X 27.6 X 50.2 | 3 | 1/5 | 307 lbs |



COMMERCIAL REFRIGERATION EQUIPMENT

IB27 FREEZER

| LIST PRICE | \$4470.00 |
|------------|-----------|
| YOUR COST | |
| NEW | \$2075.00 |
| SHOW | |
| SPECIAL | \$1250.00 |

IB27 REFREGERATOR

| LIST PRICE | \$3850.00 |
|------------|-----------|
| YOUR COST | |
| NEW | \$1680.00 |
| | |
| | |

SHOW

SPECIAL999.00

REACH-IN BOTTOM-MOUNT SERIES **FREEZER**

Features

- · CFC free refrigerant and foam insulation
- · Electronic thermostat and digital LED temperature display for accurate control and easy reading
- 3 adjustable, heavy-duty epoxy coated wire shelves per door
- · Condensate heating element built into condensate pan for efficient evaporation of excess water
- Freezer door frames have integral factory installed heating element to eliminate condensation
- Easy to mount 4" casters (lockable in front) are standard with all units
- Locking doors on all units. IB19F/27F door swing is field reversible
- · Self-closing doors that remain open at 90 degrees
- Magnetic gasket can be replaced without any tools
- · Exterior: 430 stainless steel
- Interior: 304 stainless steel
- Temperature: 0 to -10°F / -17 to -23°C
- Electrical: 115/60/1 with NEMA 5-15P plug IB81F DV: 115/208-230/60/1 with NEMA L14-20P plug, 10ft cord
- R-290 Natural Refrigerant

| 30 Natural Kerngerant | | | | | | | | |
|-----------------------|-------|--------------------------------|----------------------------------|------|-----|-------------|--|--|
| Model | Doors | Ext. Dimensions W X D X H (In) | Int Dimensions W X D X H (In) | Amps | H.P | Ship Weight | | |
| IB19F | 1 | 26.8 X 25.6 X 82.3 | 22.2 X 21.5 X 50.2 | 5 | 1/4 | 295 lbs | | |
| IB27F* | 1 | 26.8 X 32.7 X 82.3 | 22.2 X 27.6 X 50.2 | 11 | 5/8 | 329 lbs | | |

